




# Dynamic Engineers Inc.

2550 Gray Falls Dr., Suite#128, Houston, TX, 77077 USA  
 TEL: 1-281-870-8822 EMAIL: Sales@DynamicEng.com

J7 LC & &\$6 A! @S@ 8 G!%&&" , A <n!%&&  
 2.5x2.0mm 122.88MHz LVÖÜ VCXO

## Features and Benefits

- Frequency range: 122.88MHz
- Output: LVDS
- Supply voltage: 3.3V
- Current:90mA Max.
- Frequency stability vs. temperature: ±25PPM
- Operating temperature: -10°C to +60°C
- Size: 2.5x2x1mm
- Package type: SMD







## Typical Applications

- Defense Systems
- Mobile Radar Station
- Gigabit Ethernet, SONET/SDH
- Server & Storage, Data Center
- SD/HD Video, FPGA Clock Generation

## Mechanical Drawing & Pin Connections

**Drawing No:** MD240070-1



PIN	Function
#1	Control Voltage
#2	OE
#3	GND
#4	OUTPUT
#5	OUTPUT_N
#6	Supply Voltage

Unit in mm  
 1mm = 0.0394 inches

Please keep the middle area blank.  
 Do not layout any lines in this space.  
 To ensure optimal oscillator performance, place a by-pass capacitor of 0.1µF as close to the part as possible between Vcc and GND pads



# Dynamic Engineers Inc.

2550 Gray Falls Dr., Suite#128, Houston, TX, 77077 USA  
 TEL: 1-281-870-8822 EMAIL: Sales@DynamicEng.com

J7 LC & ) & \$ 6 A ! @ S @ 8 G ! % & & " , A < n ! % & & .  
 2.5x2.0mm 122.88MHz LVDS VCXO

## OSCILLATOR SPECIFICATIONS

Oscillator Specification	Sym	Condition	Value			Unit	Note
			Min.	Typ.	Max.		
Operational Frequency	f <sub>0</sub>			122.88		MHz	
<b>RF Output</b>							
Output Waveform			LVDS				
Output Level		Output high			1.6	V	
		Output low	0.9			V	
Duty Cycle			45		55	%	
Rise & Fall Time					0.35	ns	
Startup Time					8	ms	
Tri-State (Input to Pin2)		Enable	0.7 V <sub>cc</sub>			V	
		Disable			0.3 V <sub>cc</sub>	V	
<b>Power Supply</b>							
Voltage	V <sub>cc</sub>		2.97	3.3	3.63	V	
Supply Current					90	mA	
<b>Control Voltage</b>							
Control Voltage	V <sub>c</sub>		0.3	1.65	3	V	
Pulling Range			±50		±250	ppm	
Linearity					±10	%	
<b>Frequency Stability</b>							
Versus Temperature					±25	ppm	
RMS Phase Jitter		Integrated 12KHz-20MHz			300	fs	
<b>Environmental Conditions</b>							
Operating temperature range		-10°C to +60°C					